



# SEI WHALE

**All-purpose**Biobased
Epoxy System





The **Sei Whale** is one of the fastest whales, reaching speeds of up to 30 miles per hour. Sei whales inhabit all oceans and adjoining seas except in tropical and polar regions. Like other great whales, they prefer to spend the summer feeding in cooler waters before migrating to warmer waters to breed and give birth to their calves.





livingRconcept.com weR@livingRconcept.com +34 934 874 015

Follow us on @livingRconcept



## SEI WHALE

Sei Whale is a clear, all-purpose, epoxy system with high UV resistance.

All-purpose applications with variable working times for room temperature cure, with post-curing options. Easy impregnation of reinforcements and two hardener options.

#### **Applications**







Coating



Filling

#### **Key features**

Wide working temp, range



Materials and processing times should be in a range of 10-35°C.

Ideal system for:



**Transparent** applications Mix Ratio:

100:42 By Weight



### TECHNICAL DATA SHEET

#### **Processing & mechanical data**

Hardeners	Slow	Fast
Aspect	transparent liquid	transparent liquid
Viscosity @25°C mPas	40 - 80	60 - 100
Density g/cm <sup>3</sup>	0,95 - 0,99	0,98 - 1,02
Proportion by weight	42	42
Viscosity of the mixture	310 - 470	340 - 490
Pot life (100g, 25°C) min	45 - 55	12 - 17
Tensile strength мра	60 - 70	68 - 76
Tensile modulus Mpa	2600 - 3000	3000 - 3300
Flexural strength Mpa	90 - 110	95 - 115
Flexural modulus Mpa	2800 - 3100	3000 - 3300
Hardness Shore D	77 - 79	78 - 80

For technical support: Jordi Oliva

jordi@livingRconcept.com

Vadó Vila vado@livingRconcept.com



**Technologies** bonded by respect & driven by values







End-of-life solutions for the composite industry.



Repair solutions, tips, services and kits.



**Upcycling materials for** new performing composites.

REUSE



Respect for all stakeholders in the composites industry, the environment, humans & the planet as a whole.

> R\*CONCEPT livingRconcept.com weR@livingRconcept.com +34 934 874 015